


## Cat6A - SFTP - SOEPEL - PVC

Categorie	PATCH S/FTP CAT6A-4P-PVC-AM30																																																																																																																																								
Referentie	ISO/IEC 11801 TIA/EIA-568-C.2																																																																																																																																								
CPR Classificatie	Fca																																																																																																																																								
Kern	Soepel - 100% koper	<b>Technische prestaties (100m):</b>  <table><thead><tr><th>Frequentie (Mhz)</th><th>RL ≥dB</th><th>ATT ≤dB</th><th>NEXT ≥dB</th><th>DELAY ≤ns</th></tr></thead><tbody><tr><td>4.0</td><td>23.0</td><td>5.6</td><td>66.3</td><td>552</td></tr><tr><td>8.0</td><td>24.5</td><td>8.0</td><td>61.8</td><td>547</td></tr><tr><td>10.0</td><td>25.0</td><td>8.9</td><td>60.3</td><td>545</td></tr><tr><td>16.0</td><td>25.0</td><td>11.2</td><td>57.2</td><td>543</td></tr><tr><td>20.0</td><td>25.0</td><td>12.6</td><td>55.8</td><td>542</td></tr><tr><td>25.0</td><td>24.3</td><td>14.1</td><td>54.3</td><td>541</td></tr><tr><td>31.25</td><td>23.6</td><td>15.8</td><td>52.9</td><td>540</td></tr><tr><td>62.5</td><td>21.5</td><td>22.5</td><td>48.4</td><td>539</td></tr><tr><td>100</td><td>20.1</td><td>28.7</td><td>45.3</td><td>538</td></tr><tr><td>200</td><td>18.0</td><td>41.4</td><td>40.8</td><td>537</td></tr><tr><td>250</td><td>17.3</td><td>46.6</td><td>39.3</td><td>536</td></tr><tr><td>300</td><td>16.8</td><td>51.4</td><td>38.1</td><td>536</td></tr><tr><td>400</td><td>15.9</td><td>60.1</td><td>36.3</td><td>536</td></tr><tr><td>500</td><td>15.2</td><td>67.9</td><td>34.8</td><td>536</td></tr></tbody></table> <table><thead><tr><th>Frequentie (Mhz)</th><th>PSNEXT ≥dB</th><th>ELFEXT ≤dB</th><th>PSELFEXT ≥dB</th></tr></thead><tbody><tr><td>4.0</td><td>63.3</td><td>56.0</td><td>53.0</td></tr><tr><td>8.0</td><td>58.8</td><td>49.9</td><td>46.9</td></tr><tr><td>10.0</td><td>57.3</td><td>48.0</td><td>45.0</td></tr><tr><td>16.0</td><td>54.2</td><td>43.9</td><td>40.9</td></tr><tr><td>20.0</td><td>52.8</td><td>42.0</td><td>39.0</td></tr><tr><td>25.0</td><td>51.3</td><td>40.0</td><td>37.0</td></tr><tr><td>31.25</td><td>49.9</td><td>38.1</td><td>35.1</td></tr><tr><td>62.5</td><td>45.4</td><td>32.1</td><td>29.1</td></tr><tr><td>100</td><td>42.3</td><td>28.0</td><td>25.0</td></tr><tr><td>200</td><td>37.8</td><td>22.0</td><td>19.0</td></tr><tr><td>250</td><td>36.3</td><td>20.0</td><td>17.0</td></tr><tr><td>300</td><td>35.1</td><td>18.5</td><td>15.5</td></tr><tr><td>400</td><td>33.3</td><td>16.0</td><td>13.0</td></tr><tr><td>500</td><td>31.8</td><td>14.0</td><td>11.0</td></tr></tbody></table>	Frequentie (Mhz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	DELAY ≤ns	4.0	23.0	5.6	66.3	552	8.0	24.5	8.0	61.8	547	10.0	25.0	8.9	60.3	545	16.0	25.0	11.2	57.2	543	20.0	25.0	12.6	55.8	542	25.0	24.3	14.1	54.3	541	31.25	23.6	15.8	52.9	540	62.5	21.5	22.5	48.4	539	100	20.1	28.7	45.3	538	200	18.0	41.4	40.8	537	250	17.3	46.6	39.3	536	300	16.8	51.4	38.1	536	400	15.9	60.1	36.3	536	500	15.2	67.9	34.8	536	Frequentie (Mhz)	PSNEXT ≥dB	ELFEXT ≤dB	PSELFEXT ≥dB	4.0	63.3	56.0	53.0	8.0	58.8	49.9	46.9	10.0	57.3	48.0	45.0	16.0	54.2	43.9	40.9	20.0	52.8	42.0	39.0	25.0	51.3	40.0	37.0	31.25	49.9	38.1	35.1	62.5	45.4	32.1	29.1	100	42.3	28.0	25.0	200	37.8	22.0	19.0	250	36.3	20.0	17.0	300	35.1	18.5	15.5	400	33.3	16.0	13.0	500	31.8	14.0	11.0
Frequentie (Mhz)	RL ≥dB		ATT ≤dB	NEXT ≥dB	DELAY ≤ns																																																																																																																																				
4.0	23.0		5.6	66.3	552																																																																																																																																				
8.0	24.5		8.0	61.8	547																																																																																																																																				
10.0	25.0		8.9	60.3	545																																																																																																																																				
16.0	25.0		11.2	57.2	543																																																																																																																																				
20.0	25.0		12.6	55.8	542																																																																																																																																				
25.0	24.3		14.1	54.3	541																																																																																																																																				
31.25	23.6		15.8	52.9	540																																																																																																																																				
62.5	21.5		22.5	48.4	539																																																																																																																																				
100	20.1		28.7	45.3	538																																																																																																																																				
200	18.0		41.4	40.8	537																																																																																																																																				
250	17.3		46.6	39.3	536																																																																																																																																				
300	16.8		51.4	38.1	536																																																																																																																																				
400	15.9		60.1	36.3	536																																																																																																																																				
500	15.2		67.9	34.8	536																																																																																																																																				
Frequentie (Mhz)	PSNEXT ≥dB		ELFEXT ≤dB	PSELFEXT ≥dB																																																																																																																																					
4.0	63.3		56.0	53.0																																																																																																																																					
8.0	58.8		49.9	46.9																																																																																																																																					
10.0	57.3	48.0	45.0																																																																																																																																						
16.0	54.2	43.9	40.9																																																																																																																																						
20.0	52.8	42.0	39.0																																																																																																																																						
25.0	51.3	40.0	37.0																																																																																																																																						
31.25	49.9	38.1	35.1																																																																																																																																						
62.5	45.4	32.1	29.1																																																																																																																																						
100	42.3	28.0	25.0																																																																																																																																						
200	37.8	22.0	19.0																																																																																																																																						
250	36.3	20.0	17.0																																																																																																																																						
300	35.1	18.5	15.5																																																																																																																																						
400	33.3	16.0	13.0																																																																																																																																						
500	31.8	14.0	11.0																																																																																																																																						
Afscherming	SFTP																																																																																																																																								
AWG	26																																																																																																																																								
Diameter kabel	6,1 mm																																																																																																																																								
Lengte	100m																																																																																																																																								
Bandbreedte	500.0 MHz																																																																																																																																								
Buigradius	8x Diameter kabel																																																																																																																																								
Maximale trekkracht (Mpa)	≥ 13.5																																																																																																																																								
Materiaal buitenmantel	PVC																																																																																																																																								
Kleur buitenmantel	Grijs																																																																																																																																								
Aderkleuren	1 - Wit/ Blauw																																																																																																																																								
	2 - Wit/ Oranje																																																																																																																																								
	3 - Wit/ Groen																																																																																																																																								
	4 - Wit/ Bruin																																																																																																																																								
Rip-cord	Aanwezig																																																																																																																																								
Verpakking	Trekdoos																																																																																																																																								