


Cat6 - UTP - FLEXIBEL - PVC

Kategorie	U/UTP CAT6-4P-PVC	 <p>Außenmantel</p> <p>Isolierung</p> <p>Trennung</p> <p>Rip-cord</p>																																																																	
Referenz	ISO/IEC 11801 TIA-568-C.2																																																																		
CPR Klasse	Fca																																																																		
Kern	Flexibel - 100% Kupfer																																																																		
Schirmung	UTP	Technische Leistung (<30m):																																																																	
AWG	26	<table><tr><th>Frequenz (Mhz)</th><th>RL ≥dB</th><th>ATT ≤dB</th><th>NEXT ≥dB</th><th>Phase DELAY ≤ns</th></tr><tr><td>1</td><td>19.1</td><td>3.0</td><td>65.0</td><td>521</td></tr><tr><td>4.0</td><td>21.0</td><td>3.5</td><td>64.1</td><td>504</td></tr><tr><td>8.0</td><td>21.0</td><td>5.0</td><td>59.4</td><td>500</td></tr><tr><td>10.0</td><td>21.0</td><td>5.5</td><td>57.8</td><td>498</td></tr><tr><td>16.0</td><td>20.0</td><td>7.0</td><td>54.6</td><td>496</td></tr><tr><td>20.0</td><td>19.5</td><td>7.9</td><td>53.1</td><td>495</td></tr><tr><td>25.0</td><td>19.0</td><td>8.9</td><td>51.5</td><td>495</td></tr><tr><td>31.25</td><td>18.5</td><td>10.0</td><td>50.0</td><td>494</td></tr><tr><td>62.5</td><td>16.0</td><td>14.4</td><td>45.1</td><td>492</td></tr><tr><td>100</td><td>14.0</td><td>18.6</td><td>41.8</td><td>491</td></tr><tr><td>200</td><td>11.0</td><td>27.4</td><td>36.9</td><td>490</td></tr><tr><td>250</td><td>10.0</td><td>31.1</td><td>35.3</td><td>490</td></tr></table>	Frequenz (Mhz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	Phase DELAY ≤ns	1	19.1	3.0	65.0	521	4.0	21.0	3.5	64.1	504	8.0	21.0	5.0	59.4	500	10.0	21.0	5.5	57.8	498	16.0	20.0	7.0	54.6	496	20.0	19.5	7.9	53.1	495	25.0	19.0	8.9	51.5	495	31.25	18.5	10.0	50.0	494	62.5	16.0	14.4	45.1	492	100	14.0	18.6	41.8	491	200	11.0	27.4	36.9	490	250	10.0	31.1	35.3	490
Frequenz (Mhz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	Phase DELAY ≤ns																																																															
1	19.1	3.0	65.0	521																																																															
4.0	21.0	3.5	64.1	504																																																															
8.0	21.0	5.0	59.4	500																																																															
10.0	21.0	5.5	57.8	498																																																															
16.0	20.0	7.0	54.6	496																																																															
20.0	19.5	7.9	53.1	495																																																															
25.0	19.0	8.9	51.5	495																																																															
31.25	18.5	10.0	50.0	494																																																															
62.5	16.0	14.4	45.1	492																																																															
100	14.0	18.6	41.8	491																																																															
200	11.0	27.4	36.9	490																																																															
250	10.0	31.1	35.3	490																																																															
Durchmesser Kabel	5,4 mm																																																																		
Länge	100m																																																																		
Bandbreite	250.0 MHz																																																																		
Biegeradius	8x Durchmesser Kabel																																																																		
Maximale Ziehkraft (Mpa)	≥ 12.5																																																																		
Material Außenmantel	PVC	<table><tr><th>Frequenz (Mhz)</th><th>PSNEXT ≥dB</th><th>ELFEXT ≤dB</th><th>PSELFEXT ≥dB</th></tr><tr><td>1</td><td>62.0</td><td>64.2</td><td>61.2</td></tr><tr><td>4.0</td><td>61.8</td><td>52.1</td><td>49.1</td></tr><tr><td>8.0</td><td>57.0</td><td>46.1</td><td>43.1</td></tr><tr><td>10.0</td><td>55.5</td><td>44.2</td><td>41.2</td></tr><tr><td>16.0</td><td>52.2</td><td>40.1</td><td>37.1</td></tr><tr><td>20.0</td><td>50.7</td><td>38.2</td><td>35.2</td></tr><tr><td>25.0</td><td>49.1</td><td>36.2</td><td>33.2</td></tr><tr><td>31.25</td><td>47.5</td><td>34.3</td><td>31.3</td></tr><tr><td>62.5</td><td>42.7</td><td>28.3</td><td>25.3</td></tr><tr><td>100</td><td>39.3</td><td>24.2</td><td>21.2</td></tr><tr><td>200</td><td>34.3</td><td>18.2</td><td>15.2</td></tr><tr><td>250</td><td>32.7</td><td>16.2</td><td>13.2</td></tr></table>	Frequenz (Mhz)	PSNEXT ≥dB	ELFEXT ≤dB	PSELFEXT ≥dB	1	62.0	64.2	61.2	4.0	61.8	52.1	49.1	8.0	57.0	46.1	43.1	10.0	55.5	44.2	41.2	16.0	52.2	40.1	37.1	20.0	50.7	38.2	35.2	25.0	49.1	36.2	33.2	31.25	47.5	34.3	31.3	62.5	42.7	28.3	25.3	100	39.3	24.2	21.2	200	34.3	18.2	15.2	250	32.7	16.2	13.2													
Frequenz (Mhz)	PSNEXT ≥dB	ELFEXT ≤dB	PSELFEXT ≥dB																																																																
1	62.0	64.2	61.2																																																																
4.0	61.8	52.1	49.1																																																																
8.0	57.0	46.1	43.1																																																																
10.0	55.5	44.2	41.2																																																																
16.0	52.2	40.1	37.1																																																																
20.0	50.7	38.2	35.2																																																																
25.0	49.1	36.2	33.2																																																																
31.25	47.5	34.3	31.3																																																																
62.5	42.7	28.3	25.3																																																																
100	39.3	24.2	21.2																																																																
200	34.3	18.2	15.2																																																																
250	32.7	16.2	13.2																																																																
Farbe Außenmantel	Grau																																																																		
Aderfarben	1 - Weiß-Blau/Blau																																																																		
	2 - Weiß-Orange/Orange																																																																		
	3 - Weiß-Grün/Grün																																																																		
	4 - Weiß-Braun/Braun																																																																		
Rip-cord	Integriert																																																																		
Verpackung	Abrollkarton																																																																		